






BOMAR EasyCut **275.230** DG - Manual Bandsaw



Cutting Capacity:

				
90°/0°	Ø230 mm	275 x 180 mm	250 x 230 mm	230 x 230 mm
	Ø 9.05"	10.83" x 7.1"	9.84" x 9.05"	9.05" x 9.05"
45°R	Ø190 mm	190 x 150 mm	170 x 230 mm	180 x 180 mm
	Ø 7.5"	7.5" x 6"	6.7" x 9.05"	7.1" x 7.1"
45°L	Ø170 mm	185 x 100 mm	90 x 230 mm	150 x 150 mm
	Ø 6.7"	7.28" x 3.93"	3.54" x 9.05"	5.90" x 5.90"
60°R	Ø120 mm	120 x 100 mm	120 x 100 mm	100 x 100 mm
	Ø 4.72"	4.72" x 3.9"	4.72" x 3.9"	3.9" x 3.9"

Weaver Metalworking Machinery
 800 W. Lexington Rd.
 Lititz, PA 17543

Phone: 717-625-0302
 Fax : 717-625-0133
 Email: info@weavermachinery.com

The **BOMAR EasyCut 275.230 DG** manual band saw features a heavy saw frame of vibration damping cast iron with a powerful 2-speed industrial saw drive. Due to the miter cutting capability in both directions this machine is the ideal workshop machine suitable for a wide range of applications.

Simple to adjust cutting angles together with the quick-clamping vise make the operation fast and easy. The 1” saw blade guided in precise carbide guides guarantee highest accuracy. The clamping vise can be moved left to right depending on the direction of the miter cuts.

The machine can be operated as a pull-down machine where the operator guides the saw head down via a handle and trigger, or as a manual machine where the cutting force is achieved from the weight of the saw-head. In manual mode the feed rate is controlled hydraulically from the conveniently located flow-control valve.

Features:

- Rigid Cast Iron Saw Head
- Pull-down or manual operation
- 2-speed saw drive
- Miter Cutting from -45° to 60°
- Carbide Saw Blade Guides
- Safety Switches on Band-wheel Door
- Blade Tension and Breakage Switch
- Machine Switches off after Finishing the Cut
- Integrated Coolant System
- Quick-Clamping Vise
- Saw Blade Guard
- Chip Brush
- Ergonomic Design
- Simple Operation
- Including Mechanical Length Stop

Technical Data:

	Metric	Imperial
Min. Vise Opening	5 mm	0.2“
Remnant Piece Length	20 mm	0.78“
Table Height	978 mm	29.92“
Saw Band Dimensions	2,720 x 27 x 0,9 mm	8’11“ x 1- 1/16“ x 0.035“
Saw Drive	1.5 kW	2 Hp
Cutting speed	40/80 m/min	131/393 ft/min
Dimensions: width	1,150 mm	46“
length	1,588 mm	63“
height	1,477 mm	59“
Total weight	370 kg	815 lbs.
Voltage	230 V / 60 Hz / 3-phase	

Unit Price: \$ 8,500.00, f.o.b. Lititz, PA